

NYMNPA 25/02/2021

## Greenfield runoff estimation for sites

www.uksuds.com | Greenfield runoff tool

Calculated by:

Site name: Paul Goodenough

Site location: Hare & Hounds, Hawsker

This is an estimation of the greenfield runoff rate limits that are needed to meet normal best practice criteria in line with Environment Agency guidance "Preliminary rainfall runoff management for developments", W5-074/A/TR1/1 rev. E (2012) and the SuDS Manual, C753 (Ciria, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Site coordinates

Latitude: 54.45464° N

Longitude: 0.57124° W

Reference:

Date: 2019-03-11 10:31

Methodology IH124

## Site characteristics

Growth curve factor: 100 year

Total site area (ha) 0.138

## Methodology

Qbar estimation method	Calculate from SPR and SAAR		
SPR estimation method	Calculate from SOIL type		
		Default	Edited
SOIL type		4	4
HOST class			
SPR/SPRHOST		0.47	0.47
Hydrological characteristics		Default	Edited
SAAR (mm)		677	677
Hydrological region		3	3
Growth curve factor: 1 year		0.86	0.86
Growth curve factor: 30 year		1.75	1.75

2.08

2.08

## Notes:

(1) Is  $Q_{BAR} < 2.0 \text{ l/s/ha}$ ?

(2) Are flow rates < 5.0 l/s?

Where flow rates are less than 5.0 l/s consents are usually set at 5.0l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set in which case blockage work must be addressed by using appropriate drainage elements

(3) Is SPR/SPRHOST ≤ 0.3?

Greenfield runoff rates	Default	Edited
Qbar (l/s)	0.64	0.64
1 in 1 year (l/s)	0.55	0.55
1 in 30 years (l/s)	1.12	1.12
1 in 100 years (I/s)	1.33	1.33