NYM / 2011 / 0 1 4 9 / F.L 1





# **VGUARD**

# Fencing details / brochure

The most cost-effective mesh product available, ideal for basic demarcation applications. A rigid panel system with integrated profiled-beams, supplied complete with all the necessary components.

VGUARD has been designed to add an aesthetic appeal to our mesh fencing product range, a high performance system complete with excellent appearance.



## Standard Sizes

Panels				Posts Total number of fixings				
		Wire diameter V & H mm	Number of beams	Post centres mm	Inters		Corners	
Fence height mtrs	Panel size H & W				Profix bracket	Hanging bracket	Profix bracket	Hanging bracket
1.8	1733 x 2505	5mm	3	2520	5	1	10	2
2	2033 x 2505	5mm	4	2520	5	1	12	2
2.4	2433 x 2505	5mm	4	2520	6	1	12	2

Heights above the standard range can be achieved using a multi-lift system.

#### Panel

Manufactured using 5mm wire welded at each intersection complete with inserted beams creating a strong and durable panel, the mesh aperture consists of a  $200 \times 50$ mm mesh spacing providing excellent see through visibility!

## Post System

Standard posts are manufactured from  $60 \times 60 \times 2.5 \text{mm}$  Rolled Hollow Section. All posts include threaded inserts, leaving a clean and flush design to the rear face. Specially designed PROFIX Securing system brackets are used for quick and easy installation.

## Applications

The VGUARD system is suitable for most applications were general site demarcations is required typical examples are uses in schools, public areas, commercial businesses & retail outlets.

## Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with rear hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions complete with anti-climb PROTECTORGATE slide latch. See our gate range for further details.

